NAGEMENT FOR THE MONTH OF MAY, 2022

ii) Shredder - 1 No. Capacity: 50 -100 kg iii) Shredder - 1 No. Capacity: 50 -100 kg iv) Needle Destroyer - 12 Nos. v) ETP - 1 No Capacity: 4000 litre/day	c) Total nos. And capacity of each treatment equipment (in Kg/day)	
		7
iii) Shredder iv) Needle Destroyer v) ETP (Effluent Treatment Plant)	b)Details of treatment equipment	
i) Incinerator ii) Autoclave	a)Bio-medical waste treated (in Kg/day)	
8.5 Kg	In case, HCF is having captive treatment facility,	
	applicable)	6
N/A	treatment facility) Name and address of the CBWTF through which waste is disposed off (as	5
Through captive treatment facility	Quantity of bio-medical waste generation (in the control of through captive Mode of disposal of bio-medical waste (through CBWTF or through captive	4
8.5 Kg	1974 and Air(Prevention and Control of Foliation)	
Applied for, Application No: WB/TEZ/T-1745/18-19/01/1489 Previous authorization No: WB/TEZ/T-1745/18-19/01/1489	b) Consent under Water (Prevention and Control of Pollution) Act,	ω
Previous authorization no: 444804, dated, 12/03/2021	sation under BMWM Rules, 2016	
Applied for, Application no. 47760, WB/OTWA/BMW-448/18-19/01/170	Details of:	
	No. of Beds	2
336 No.	Contact Address and details of the ricalment's and details and det	1
Pin-784001, Tele No. 03712-232652, fax No 03/12-233023		Sl. No.
CD Begional Institute of Mental Health, Tezpur, Sonitpur, Assam,	Description	
Remarks	REPORT ON BIO-MEDICARE	
FOR ITE MACE	ON THE MEDICAL WASTE MANAGEMENT FOR THE FIGURE	

The de single of the state of t

9	∞		
No. of trainings conducted on Bio-medical Waste management in the current	Monthly records of biomedical waste generation(category wise)	d) Operating parameters of the treatment equipment as per BMWM Rules, 2016	
28	i) Yellow category: 84.441 kg/month ii) Red category: 136.121 kg/month iii) White category: 5.748 kg/month iv) Blue category: 28.107 kg/month	Sl. No. Parameter Result Sl. No. Parameter i. SO ₂ (ppm) iii. NO ₂ (ppm) iii. NO ₂ (ppm) 29 iii. HCI (mg/Nm3) 29 remperature Primary Chamber 800° ± 50° C, Secondary Chamber 1000° ± 50° C Height- 30 meters above from the ground Capacity- 10-12 Kg/hr 2) Autoclave: (Gravity flow) ii) Monitors steam processes with Geobacillus stearothermophilus spores. iii) Steam Indicator tape	1) Incinerator

I/C Central Laboratoryal MH LGBRIMH, Texpor BRIMH

year